

www.fowlerprecision.com at n S Visit

# **HEIGHT GAGES**

TOOL-A-THON Vol. 17.1

L

#### Fowler-Trimos V3, V4 & V5 Electronic Height Gages

The Fowler-Trimos V3, V4 and V5 vertical measuring instruments have been developed for the most difficult workshop environments. Manufactured in their entirety in Switzerland, they guarantee a robust, precise and reliable product in the long run.



2

Probe Sets 54-199-105-0

54-199-106-0

54-199-107-0

Prices & Specifications are subject to change without notice.

\$1679.94

1253.58

445.00

\$1595.00

1190.00

420.00

4mm Probe Set, 21 piece

8mm Probe Set, 16 piece

Economy Probe Set, 7 piece

## **HEIGHT GAGES - Accessories**

#### Fowler-Trimos Height Gage Probe Kits

#### 4mm Probe Set

Case	
54-199-502-0	Disc-shaped insert Ø 7.7mm
	Disc-shaped insert Ø 11.5mm
54-199-503-0	Corner insert 1mm
54-194-948-0	Measuring insert holder for: M2.5, M1.6, M1.4
54-199-507-0	Insert holder L=80mm M2.5
54-199-508-0	Insert holder 90° L=80mm Ø 4mm
54-199-512-0	Measuring insert holder Ø 1mm
54-199-509-0	Ruby Ball Probe Ø 2mm
	Ball Probe Ø 1mm
54-199-510-0	Knife-edged measuring probe L=88mm
54-199-019-0	Holder with reduction 8mm/4mm
54-194-935-0	Swivel holder Ø4/Ø8mm
Hemispheric probe	
Probe with pin (plus 4	additional pins)
Test indicator tip Ø 1m	nm í í
Test indicator tip Ø 2m	
Test indicator tip Ø 3m	
Key for ball insert	54-199-105-0
Hex wrench 1.5mm	
Hex wrench 2.5mm	

#### 8mm Probe Set

Case 54-194-910-0 Carbide Ball Probe Ø 4mm L 140mm Carbide Ball Probe Ø 2mm 54-194-906-0 54-194-912-0 Carbide Probe with pin Ø 1.5mm Swivel holder 90° Ø 4mm 54-194-938-0 54-194-942-0 Measuring insert holder Ø 2mm 54-194-930-0,931-0 Insert holder (metric) M2.5 54-199-505-0 Insert holder L=124mm M2.5 Insert holder L=200mm M2.5 Hemispheric probe tip Disc-shaped insert Ø 18mm Test indicator tip Ø 1mm Test indicator tip Ø 2mm Test indicator tip Ø 3mm Key for ball tip Hex wrench 2.5mm

54-199-106-0

#### **Economy Probe Set**

Case	
54-199-503-0	Corner insert 1mm
54-199-504-0	Measuring insert M2.5 with ball contact
54-199-515-0	Hex wrench 2.5mm
54-194-906-0	Carbide ball probe Ø 2mm
54-194-942-0	Measuring insert holder Ø 2mm
54-194-938-0	Measuring insert holder 90°, Ø 4mm, L= 65mm

#### 12"/300mm Probe Holder

	54-199-400-0	-	54-199-107-0
Order No.	Description	List Price	Sale Price
54-199-105-0	4mm Probe Set, 21 piece	\$1679.94	\$1595.00
54-199-106-0	8mm Probe Set, 16 piece	1253.58	1190.00
54-199-107-0	Economy Probe Set, 7 piece	445.00	420.00
54-199-400-0	12"/300mm Holder – for 8mm probes	940.34	890.00



# **HEIGHT GAGES**



54-930-217-0

**FREE** 1mm Ball Probe with 6"/150mm & 12"/300mm Hi\_Cal Purchase

	Order No.	Range	Accuracy	List Price	Sale Price
	54-931-150-0	6"/150mm	0.00013"/0.0034mm	\$4661.50	\$4160.00
	54-931-300-0	12"/300mm	0.00016"/0.0042mm	5357.04	4850.00
	54-931-450-0	17.5"/450mm	0.00020"/0.005mm	5608.98	5100.00
	Accessories				
	54-930-215-0	Full Probe Accessory Set		\$1093.95	\$975.00
	54-930-217-0	Basic Probe Accessory Set		593.64	530.00
Ľ					

-owler TOOL-A-THON Vol. 17.1

Find us on social media!

ļ

**.** 

IJ

4-

# **HEIGHT GAGES**

### Hi Gage One


The Fowler-Sylvac measuring system is exceptionally fast (60" per second traverse) and is the most reliable and maintenance free system ever created for measurement

- True inch/metric conversion
- Resolution: 0.0005"/0.01mm
- . Repeatability: 0.0004"/10µm
- Base size: 5.6" wide x 6.8" length
- Accuracy 0.0016"/0.002"
- Includes scriber/measuring probe
- Direct RS-232 output
- Scale not affected by oil, dust, chips, magnetism, shock, etc.

-8

00

List \$401.60



### Electronic **Height Gage**

An economical height gage that offers high quality, accuracy and durability.

- · Large base for easy movement
- True inch/metric conversion
- Range: 0 20"/500mm
- Resolution: 0.0005"/.01mm
- Accuracy: ± 0.0025"
- · Repeatability: 0.0005"/0.01mm (±2s)
- · Deluxe wooden case with reinforced metal edges
- Large easy to read LCD Non-glare chrome reading
- surface
- Overall height: 28"
- Beam thickness:1.25 X 0.4"

Order No. 54-106-020-0

Sale \$258.

Presetable display

## Twin Beam Dial **Height Gages**

- Separate digit counters register both upward & downward travel.
- Zero setting can be obtained throughout the gage's range.
- Coarse readings in 0.100" graduations: fine readings taken on indicator are 0.001"
- Dual chrome plated beams Carbide-tipped scriber.
- · Base is hardened. ground & lapped for
- maximum flatness.

Accuracy 52-174-212-0 ±0.0015" 52-174-224-0 ±0.002"

> 52-174-212-0 Range

> > 12"

24"

List Price

\$355.25

723.68

us on social П media Sale Price Į \$295.00

52-174-224-0 Prices & Specifications are subject to change without notice.

Order No.

52-174-212-0

**595.00** 

Super Smooth Movement!

FOOL-A-THON Vol. 17.1

## LIFETIME WARRANTY



Order No.	Description	Maximum Error	Resolution	List Price	Sale Price
54-530-125-0	0 - 0.500"/12.5mm	0.0004"/0.01mm	0.0005"/0.01mm	\$430.75	\$387.50
54-530-135-0	0 - 0.500"/12.5mm	0.00012"/0.003mm	0.00005"/0.001mm	535.81	482.00
54-530-145-0	0 - 1"/25mm	0.0004"/0.01mm	0.0005"/0.01mm	491.64	442.00
54-530-155-0	0 - 1"/25mm	0.00016"/0.004mm	0.00005"/0.001mm	588.34	529.50
54-530-175-0	0 - 2"/50mm	0.00019"/0.005mm	0.00005"/0.001mm	1113.64	1002.00
Bluetooth					
54-530-335-0	0 - 0.500"/12.5mm	0.00012"/0.003mm	0.00005"/0.001mm	682.89	614.60
54-530-355-0	0 - 1"/25mm	0.00016"/0.004mm	0.00005"/0.001mm	730.22	657.20
Accessories					
54-115-246-BT	USB Bluetooth Rec	eiver		47.33	42.60
Analog Display					
54-530-535-0	0 - 0.500"/12.5mm	0.00012"/0.003mm	0.00005"/0.001mm	619.85	557.80
54-530-555-0	0 - 1.00"/25mm	0.00016"/0.004mm	0.00005"/0.001mm	677.69	608.00

Find us on social media!

Prices & Specifications are subject to change without notice.

6



Prices & Specifications are subject to change without notice.

7

# **HIGH RESOLUTION**





#### **HIGH RESOLUTION** S Dial Pro **High Accuracy Indicators** Wler TOOL-A-THON Vol. 17.1 NEW! 0.00001"/0.0002mm repeatability 0.000005"/0.0001mm resolution 0.00006"/0.0015mm accuracy • 2"/50mm range 54-530-700-0 Mixed ceramic bearing/ball bearing system Includes spindle lifting attachment IP54 rated Available with or without spring tension svivad 8mm or 25mm mounting diameter 54-530-705-0 Swiss Qualitu! owle PROXIMITY INTERFACE Find ESISTANT & FLUID owler POWER Π INTERFACE 5 Order No. List Price Description Accuracy Resolution Sale Price 54-530-700-0 0.000005"/0.0001mm \$2350.00 8mm mount with spring 0.00006"/0.0015mm \$2652.80

Prices & Specifications are subject to change without notice.

0.000005"/0.0001mm

0.000005"/0.0001mm

0.000005"/0.0001mm

0.00006"/0.0015mm

0.00006"/0.0015mm

0.00006"/0.0015mm

54-530-705-0

54-530-710-0

54-530-715-0

25mm mount with spring

8mm mount without spring

25mm mount without spring

9

2350.00


2350.00

2350.00

2652.80

2652.80

2652.80





Gra	ade	Ø	

- Each block certified to N.I.S.T.
- Each block is individually serialized
- Sizes clearly marked on each block
- · Complete with fitted wooden case

#### 53-670-038-0

Order No.	Description	List Price	Sale Price
53-670-038	36 piece Grade Ø Rectangular Gage Block Set	\$461.03	\$320.00
53-670-080	81 piece Grade Ø Rectangular Gage Block Set	848.41	650.00

# **X-Glide** Lubricant and Protectant

- · Specifically formulated for precision tools
- Synthetic lubricant enriched with multiple anti-friction additives
   Sub-micron particle size allows for maximum penetration and
- durability
- Antistatic additive prevents the attraction of dust and dirt
   Contains no solvents, propellants or flammable gases
- Contains no
   PH neutral
- 2.5 oz. spray bottle

**FREE** with any <u>above</u> Gage Block Set Purchase!

#### Order No. 53-885-105-0

Sale



2 fl. ozs./60 ml.

10

Prices & Specifications are subject to change without notice.

List \$10.51

Find us on social media


,**j** 

**.** 

IJ

4-

#### Long Rectangular Gage Blocks



53-670-777-0 holding clamp set used for holding two large blocks together

 Fowler's long gage blocks are rectangular in shape, Grade Ø and supplied with an NIST certificate
 Stackable using holding clamps



Order No. Description List Price Sale Price 53-675-216-0 5" Gage Block \$169.58 \$144.00 53-675-218-0 6" Gage Block 205.91 174.00 53-675-220-0 7" Gage Block 236.25 200.00 53-675-222-0 8" Gage Block 223.00 266.49 53-675-224-0 10" Gage Block 302.82 255.00 12" Gage Block 53-675-226-0 320.99 270.00 375.48 53-675-228-0 16" Gage Block 310.00 20" Gage Block 53-675-230-0 478.49 400.00 53-670-008-0 8 piece Gage Block Set 1781.69 1625.00 53-670-777-0 Holding Clamp for two large blocks 97.61 72.00

#### Large Square Gage Blocks

Grade Ø

.

- NIST Traceable
- · Vertically more stable then rectangular blocks
- Large sizes help eliminate block stacks
- Meets or exceeds Federal Specifications ASME B89.1.9-2002

Order No.	Description	List Price	Sale Price
53-676-216-0	5" Large Square Gage Block	\$226.07	\$190.00
53-676-218-0	6" Large Square Gage Block	271.43	230.00
53-676-220-0	7" Large Square Gage Block	311.43	260.00
53-676-222-0	8" Large Square Gage Block	367.71	310.00
53-676-224-0	10" Large Square Gage Block	511.56	430.00
53-676-226-0	12" Large Square Gage Block	568.89	480.00
53-676-228-0	16" Large Square Gage Block	854.39	720.00
53-676-230-0	20" Large Square Gage Block	996.03	840.00



**QUICK CHECK** Multi-Function Check Standard

# Find us on social media <u>د</u> L) 4

j



- · One compact, multi-function, precise standard
- · Can be used to check and verify a multitude of measuring instruments
- · Checks calipers, micrometers, depth gages, bore gages, test and dial indicators, caliper gages, height gages, protractors, combination sets and more
- · Supplied with a manufacturer's test certificate and fitted wood case · All sizes marked are actual

Sale \$1320.00

Order No. 53-813-015-0




List \$1580.74

# Wer TOOL-A-THON Vol. 17.1

## **Setting Masters**

Fowler's Setting Masters are quick, easy and extremely accurate. Each comes with a manufacture's certificate of calibration and a wood case. Save time and money by calibrating your own measuring tools.



12

#### **Micrometer Calibration Set** with steel blocks & optical flats



- 11 Pc. 9 rectangular gage blocks and two optical flats.
- Includes NIST Certificate
- · Assists in meeting both Federal specification GGG-C-105c and ISO 9000 requirements.
- · Contains one block of each of the following sizes: 0.0625, 0.100, 0.125, 0.200, 0.250, 0.300, 0.500, 1.000 & 2.000"
- TWO OPTICAL FLATS that vary in size by .0125" which allows checking anvil faces at half revolutions of spindle for checking flatness and
- parallelismSupplied with fitted wooden case

Order No. 53-670-002-0

#### ale \$215.00 List \$265.02

## Caliper, Micrometer, Snap Gage Checking Set

Fowler's setting master is quick, easy and extremely accurate. It comes with a certificate of calibration and a fitted aluminum case. Save time and money by calibrating your own measuring tools quickly and easily.

#### Set Includes:

- Calibration certification traceable to N.I.S.T. standards
- Stand height: 12.5"
- 9 pc. Grade AS-0 gage block set (sizes: 0.625", 0.100", 0.125", 0.200", 0.250", 0.300", 0.500", 1.000" & 2.000"
- Certificate of calibration is traceable to N.I.S.T. stan-

Worn blocks can be easily replaced!


- dards & provides the individual deviation of each block
- Optical flat (flatness: 0.000004" ; Parallelism: 0.00002")
- 4.0mm ball end T-handle hex wrench

us on socia П Į

Order No.	Description	List Price	Sale Price
53-813-001-2	Complete caliper, Micrometer and Snap Gage Checking Set	\$327.92	\$250.00
53-813-002-0	Mic Checker Holder without Blocks	164.34	145.00

**Pin Gage Set** 







Prices & Specifications are subject to change without notice.

15

us on social

## **VERNIER CALIPERS**

j **Light Line Vernier Calipers** NEW <u>ב</u>. L 10 20 30 40 50 60 70 60 90 10 110 120 130 140 150 160 170 180 200 210 1 2 3 4 5 4 7 6 9 1 2 3 4 5 4 7 6 9 1 2 3 4 5 6 7 6 9 4 1 3 4 5 6 7 6 9 1 2 3 4 5 6 7 6 9 1 2 3 4 5 6 7 6 9 1 2 4 52-075-150-0 · Light weight beam made of oxide coated aluminum · Stainless steel jaws, hardened and finely ground with knife edge top jaws (3.5"/90mm length) · Spare jaws can be modified and exchanged with standard jaws for special applications · Parallax free vernier scale for ease of reading High contrast white numbering on black anodized frame Inch and metric graduations (0.001"/0.05mm) Made in GERMANY

Order No.	Description	Accuracy	List Price	Sale Price
52-075-018-0	NEW 19"/500mm	0.001"/0.03mm	\$360.00	\$342.00
52-075-035-0	NEW 35"/900mm	0.0015"/0.04mm	650.00	617.00
52-075-150-0	NEW 6"/150mm - Replace	cement Jaws	100.00	95.00

#### **Master Vernier Calipers**

Fowler 0,23		STANLESS PL22555151412145	
	•	52-085-012-0	
	ne finish on all m stainless steel th		


- Extra long vernier scales
- · Machine divided and engraved from master for exceptional accuracy
- Open face design permits both vernier scales to be located on one side of the gage for both inside and outside measurements
- · All sizes permit inside and outside measurements
- · For larger workpieces, the long jaws permit greater accessibility and easier measurements

Order No.	Description	Graduation	Jaw Depth	List Price	Sale Price
52-085-012-0	12"/300mm	0.001"/0.02mm	3"	\$174.69	\$131.00
52-085-024-0	24"/600mm	0.001"/0.02mm	4"	370.70	275.00
52-085-040-0	40"/1000mm	0.001"/0.02mm	5-1/2"	867.36	645.00
52-085-060-0	60"/1500mm	0.001"/0.02mm	7-1/2"	2432.86	1750.00

Find us on social media!

16

#### **DIAL CALIPERS** COL-A-THON **Machinist Grade Dial Calipers** BEST SELLER! WIOR Case of the ER HIGH P 52-008-706-0 111 TOOL-A-THON Vol. 17.1 4-way measuring 52-008-707-0 Solid stainless steel construction 0.100"/2mm range per revolution 0.001"/0.02mm reading dial face Tough shockproof gearing Dial Face List Sale Order No. Description Color Price Price 52-008-706-0 White \$74.78 \$55.00 0 - 6 0 - 6" 52-008-707-0 Black 74.78 55.00 52-008-709-0 0 - 150mm (Metric Model) Yellow 74 78 55.00 52-008-708-0 0 - 8" White 93.83 73.00 Dial Cal Plus Protected RESISTAN 52-008-050-0 IP54 rated against fluid and debris Carriage lock screw 4-way measurement · Heavy duty stainless steel frame - 4mm thick 0.100" per revolution Adjustable bezel with lock Thumbroll for fine adjustment Order No. Description Accuracy Graduation List Price Sale Price 52-008-050-0 0 - 6" - White-face ± 0.001" 0.001" \$118.45 \$99.00 52-008-051-0 0 - 6" - Black-face ± 0.001" 0.001" 118.45 99.00 52-008-052-0 0 - 150mm - White-face ± 0.03mm 0.02mm 118.45 99.00 0-6" Dial Calipers



White

52-008-007-0

Prices & Specifications are subject to change without notice.

17

50.45

89.71

us on social

media


Π

5

## **DIAL CALIPERS**

90 0 10 90 20	
	นอนหมดของรับบทุสาสาสาร์บนสาสารการที่บองคนจากหนับอนุสมธรรมหรือ excess excess
	52-008-009-0
	0.1" per revolution
	Covered rack     Thumbroll, carriage lock and adjustable bezel
	Hardened stainless steel

Order No.	Range	Accuracy	Graduation	List Price	Sale Price
52-008-009-0	0 - 8"	± 0.0015"	0.001"	\$135.45	\$1 <b>04.95</b>
52-008-013-0	0 - 12"	± 0.002"	0.001"	173.45	85.95



Order No.	Range	Jaw Length	List Price	Sale Price
52-025-108-0	8" Caliper	2.5"	\$136.06	\$78.00
52-025-112-0	12" Caliper	2.875"	197.86	129.00

Col-A-THON **Extended Range Dial Calipers** BEST SELLER! LER HIGH P 52-008-018-0 Graduations: 0.001" Stainless steel construction Satin chrome finish Depth rod 0.500" internal measuring nibs Order No. Depth of Jaws List Price Range Sale Price \$247.10 \$154.00 52-008-018-0 18" Caliper 3.125'

52-008-024-0

18

Prices & Specifications are subject to change without notice.

3.375"

24" Caliper

299.42

232.00

# ELECTRONIC CALIPERS





Fowler

54-101-150-2

NEW!

54-101-600-1

Fowler



NEW Caliper Design for 54-101-150-2 Model!

#### Now available with optional N.I.S.T. Certification!

Accuracy: 0.001"/0.02mm (6" models)

- Stainless steel frame
- Large easy-to-read display
- Resolution: 0.0005"/0.01mm
- Direct inch/metric conversion
- Absolute/Incremental Measurement
- 4-way measuring
- Also available with super large display

Order No.	Range	Display Type	List Price	Sale Price
54-101-150-2	6"/150mm	Regular Display	\$47.79	\$35.00
54-101-150-C	6"/150mm	<b>Regular Display with N.I.S.T Certi</b>	ficate	68.00
54-101-600-1	6"/150mm	Super Large Display with hold feature	59.43	39.60
54-101-800-1	8"/200mm	Super Large Display with hold feature	89.10	67.00
54-101-900-1	12"/300mm	Super Large Display with hold feature	118.97	89.00

**Poly-Cal**<sup>®</sup> Electronic Caliper

Polycarbonate Caliper Includes • Fractional Measurement • Easy-To-Read Display • Lightweight frame

Sale \$17.50

Order No. 54-101-175-0

• Range 6"/150mm

Absolute Reading!

Fowler

- Polycarbonate frame
- Resolution 0.0005"/.01mm (Fractions by 1/64" increments)
- Absolute/Incremental Measurement
- Direct inch/metric/fraction conversion
- 4-way measuring
- Accuracy ± 0.008"

List \$26.06

Supplied with clip-on vinyl pouch





## **ELECTRONIC CALIPERS**

#### Wireless Transmitter For Economy Calipers & IP54 Calipers

Wireless Transmitter allows wireless input from Economy and IP54 Economy Calipers (below) as well as Indi-Max Indicators (pg. 43). Input directly in to Excel, Word, Cad and Notepad.

- · Includes 1 USB receiver and 1 Transmitter (good for 1 tool)
- Audible as well as LED indications when data is sent
   Input into Excel, Word, Notepad and CAD programs with the press of a button.
- Simple plug and play operation
- Wireless technology allows the use of the tool up to 60 feet away from a computer




Economy Calipers 🟹 Indi-X Indicators (pg.43)

Order No. 54-115-100-0




List \$99.50

Fowle



Order No.	Range	List Price	Sale Price
54-100-004-2	0 - 4"/100mm Caliper	\$99.81	\$59.85
54-100-000-2	0 - 6"/150mm Caliper	116.39	78.00
54-100-008-2	0 - 8"/200mm Caliper	136.68	107.50
54-100-112-2	0 - 12"/300mm Caliper	178.19	123.00
54-520-399-0	Data Cable	152.90	140.00





## **ELECTRONIC CALIPERS**


## **Light Line Electronic Calipers**



- Includes a fitted case, instructions and test certificate.
- · Replacement jaws available

	Order No.	Range	Accuracy	List Price	Sale Price
	54-112-012-0	NEW 0 - 12"/300mm	0.0015"/0.04mm	\$295.00	\$280.00
H	54-112-030-0	NEW 0 - 31"/800mm	0.002"/0.06mm	680.00	645.00
	52-075-150-0	6" Replacement Jaws		100.00	95.00

Made in GERMANY



DWIEr TOOL-A-THON Vol. 17.1

Prices & Specifications are subject to change without notice.

0.004"/10mm

1229.61

695.00

4.9"



Swiss Quality!

#### Alternative jaws available, contact the Fowler Technical Department for more information 1-800-788-2353

INTERFACE

pecifications	54-110-512-0	54-110-524-0	54-110-540-0	54-110-560-0	54-110-580-0	54-110-600-0	
leasuring Range	0-15"/0-400mm	0-24"/0-600mm	0-40"/0-1000mm	0-60"/0-1500mm	0-80"/0-2000mm	0-100"/0-2500m	
laximum Error	30µm/0.0012"	40µm/0.0016"	50µm/0.002"	90µm/0.0035"	120µm/0.0048"	200µm/0.0078"	
lepeatability		20µm/0.0008" 30					
leasuring Force		5 - 10 N					
onnection		Bluetooth Smart/Proxi RS-232 or - USB					
Protection Rating		IP67 (Electronic Module)					
Preset Max.		±9999.99 mm / ±399.9995 IN					
Veight	1.5 kg	1.6 kg	1.9 kg	2.3 kg	2.6 kg	2.9 kg	
Order No.	Des	scription			List Price	Sale Price	
54-110-512-0	0-1	5"/0-400mm Ultr	alight IV		\$2128.23	\$1810.00	
54-110-524-0	0-2-	4"/0-600mm Ultr	alight IV		2482.99	2060.00	
54-110-540-0	0-4	0"/0-1000mm UI	tralight IV		2857.63	2325.00	
54-110-560-0	0-6	0"/0-1500mm UI	tralight IV		4296.95	3585.00	
54-110-580-0	0-8	0"/0-2000mm UI	tralight IV		5920.18	5030.00	
54-110-600-0	0-1	00"/0-2500mm l	Jltralight IV- speci	al order	7154.59	6080.00	
Cables							
54-115-526-0	Pro	ximity USB Cab	le		\$136.07	\$122.00	
	Pro	ximity Serial Cal	ble		136.07	122.00	
54-115-526-0 54-115-527-0 54-115-246-BT		B Bluetooth Rec			47.33	42.60	

us on socia Π

5



			MICROM	ETERS		
	0.5.1.0					
	0.5 00		icrometer	chrome finisi • Anvil and spi ground with • Clear, crisp g thimble • Diameter of the spin of the	ometer by 0.001 h ndle hardened a microlapped en graduations on b measuring faces	and precisior ds. parrel and
ч	Fowler		Order No. 52-230	-000-0		
	0-0.6" 0.00		Sale	<i>\$29</i> .	<b>50</b> List \$	33.82
	Outside	e Micron			OL	A-THON
		w	vith Decimal Equ	ivalents on F	rame o	CELLER!
			- 15		BES	Strungs
			10		row	ER HIGH PREC
	4116 1 250 1 2750 1	20015 1 5122 7 2017 7 2017 1 3425 1 3425 1 3425 1 3426 1 5312 1 532 1 53	52-235-001-1	chrome fir • Graduation	mal equivalents hished forged ste	on satin eel frame
	7 9 5655 0-1" .0001" 13 8255 13 8255 31	25 7187 25 7812 27 9437 29 9062	Order N	o. Range	List Price	Sale Price
<b>~</b>			52-235-0 52-235-0		\$60.70 73.70	\$42.00 51.00
			52-235-0		87.81	61.50
OL-A-THON Vol. 17.1	Outside		licrometers	Carbide tip     Graduation     Diameter c     Positive lo     Anvil & spi	of measuring fac	ces: 0.256" and precisior
$\leq$	Order No.	Range	Accuracy	Thimble	List Price	Sale Price
	52-253-001-1 52-253-101-1	0 - 1" 0 - 1"	± 0.001"	Friction	\$33.60	\$20.00
$\bigcirc$	52-253-101-1	U - 1"	± 0.001"	Ratchet	33.60	20.00
Õ	Digit C	ounter I	Nicrometer	S		
Ver'		0.2.3 4 °	52-224-001-0	Digital cc     Resolutio     Microfine     Carbide t	ounter reads to 0 on: 0.0001" (usir graduations on ipped measurin or 1" include sta	ng vernier) satin chrom g faces
Z			Orden	lo Bongo	List Drice	Sala Dries
0	Fowle		Order 1 52-224-	001-0 0 - 1"	List Price \$109.23	Sale Price \$70.00
	0-1″ 0.0	001	52-224-		114 84	73.50

Prices & Specifications are subject to change without notice.

52-224-002-0

52-224-003-0 52-224-004-0

1 - 2"

2 - 3" 3 - 4"

114.84

130.80

143.88

73.50

83.70

92.00

24

	MICROME	TERS	
Resolution: 0.00005"/ Accuracy: ± 0.00016" Direct RS-232 output Carbide measuring fa	/0.004mm (up to 2")		-870-001-0
Absolute and increme Ratchet thimble	ental modes	Mer . 00005 <sup>-</sup> Ball Attachment	IP40)
Order No.	Range	List Price	Sale Price
4-870-001-0	0 - 1"/0 - 25mm	\$89.10	\$65.50
4-870-002-0	1 - 2"/25 - 50mm	90.23	67.50
4-870-003-0 4-870-004-0	2 - 3"/50 - 75mm 3 - 4"/75 - 100mm	105.99 112.48	79.30
Protected to IP54 spe automatic switch off accuracy: ± 0.00016"/	.004mm (up to 2")		Sale Price         \$65.50           \$75.50         84.00           860-001-1         \$65.50           Pricetet to:         \$65.50           Pricetet to:         \$89.00           103.00         113.00
Resolution: 0.00005"/	0.001mm	ON OF SET ASS <sup>®</sup> EVEN	
Direct RS-232 output Carbide measuring fa	ces	FREE!	Protected to:
bsolute & incrementa	al modes		COLANT & FLUE RESISTANT
Order No.	Range	List Price	Sale Price
4-860-001-1	0 - 1"/0 - 25mm	\$112.89	\$89.00
4-860-002-1 4-860-003-1	1 - 2"/25 - 50mm 2 - 3"/50 - 75mm	130.71 142.55	103.00 - • 112.00 - •
4-860-004-1	3 - 4"/75 - 100mm	166.35	131.00
4-860-005-1	4 - 5"/100 - 125mm	185.30	144.50
4-860-006-1	5 - 6"/125 - 150mm	207.96	163.00
4-860-103-1	0 - 3"/0 7 -5mm Set	371.32	285.00
Micromete	52-247-000-0		
	Provides a measuring po angle for outside microm other instruments.		
C. C			
		52-247-005-0	
TRA MAG			meter stand to
SHIES CONTRACTOR	an	ique locking nut adjusts micron y position for perfect use and v and folds for storage.	
477	Use at machine stations, steel ta	0-12" micrometers firmly to me centers, work, assembly and i ables and shelves unting on cylindrical surfaces	
	Micrometer • On/Off magnet s		5
order No.	Description	List Price	Sale Price
2-247-000-0	Adjustable Micrometer S		\$36.50
52-247-005-0	Folding Micrometer Stan	d 38.08	27.00

Prices & Specifications are subject to change without notice.

Magnetic Micrometer Stand

52-247-010-0

27.00 40.00 25

38.08 51.00

official find us on social medial **3345 Ef Le in 幽** 



- · Carbide anvils
- Extended Range 0-30mm, 30-66mm and 66-102mm

0-4" Range with ONLY 3 Mics!

Description	Max Error	List Price	Sale Price
0 - 1.18"/0 - 30mm	0.00012"/0.003mm	\$514.79	\$410.00
1.18" - 2.6"/30 - 66mm	0.00016"/0.004mm	761.74	695.00
2.6" - 4.0"/66 - 102mm	0.00020"/0.005mm	1065.29	945.00
0 - 1.18"/0 - 30mm	0.00012"/0.003mm	761.74	645.50
0 - 4"/0 - 102mm		2353.34	1995.00
Description			
Proximity cable with USB c	connection	\$136.07	\$122.00
		136.07	122.00
USB Bluetooth receiver		47.33	42.60
	0 - 1.18"/0 - 30mm 1.18" - 2.6"/30 - 66mm 2.6" - 4.0"/66 - 102mm 0 - 1.18"/0 - 30mm 0 - 4"/0 - 102mm <b>Description</b> Proximity cable with USB of Proximity cable with serial	0 - 1.19"/0 - 30mm 0.00012"/0.003mm 1.18" - 2.6"/30 - 66mm 0.00016"/0.004mm 2.6" - 4.0"/66 - 102mm 0.00020"/0.003mm 0 - 1.18"/0 - 30mm 0.00012"/0.003mm 0 - 4"/0 - 102mm Description Proximity cable with USB connection Proximity cable with serial connection	0 - 1.18"/0 - 30mm         0.00012"/0.003mm         \$514.79           1.18" - 2.6"/30 - 66mm         0.00016"/0.004mm         761.74           2.6" - 4.0"/66 - 102mm         0.00020"/0.005mm         1065.29           0 - 1.18"/0 - 30mm         0.00012"/0.003mm         761.74           0 - 4"/0 - 102mm         2353.34           Description         2353.34           Proximity cable with USB connection         \$136.07           Proximity cable with serial connection         136.07

#### Electronic IP54 Ball Anvil & Spindle Micrometers

	Fowler 0-1* 0.00	CHURCH AND	54-860-113-1		9555 185-11/m	
	curved surface Ball anvil/flat s the insides of Large LCD dis Automatic swi Hardened stee	spindle for measuring holes to outer edges splay, 8.5mm	g tubes or	Fowler 1" 0.00005"	Protected I IP54 column a Ru RESISTAN	•
	Order No.	Range	Resolution	Accuracy	List Price	Sale Price
	Ball Anvil Micro			,		
	54-860-113-1	0 - 1"/0 - 25mm	0.00005"/0.001mm	0.00016"/0.004mm	\$114.40	\$97.20
	54-860-114-1	1 - 2"/25 - 50mm	0.00005"/0.001mm	0.00016"/0.004mm	134.00	113.90
	54-860-115-1	2 - 3"/50 - 75mm	0.00005"/0.001mm	0.0002"/0.005mm	153.90	130.80
	54-860-116-1	3 - 4"/75 - 100mm	0.00005"/0.001mm	0.0002"/0.005mm	173.40	147.30
	Ball Anvil & Sp	indle Micrometers				
	54-860-211-1	0 - 1"/0 - 25mm	0.00005"/0.001mm	0.00016"/0.004mm	\$124.70	\$106.00
1	54-860-212-1	1 - 2"/25 - 50mm	0.00005"/0.001mm	0.00016"/0.004mm	143.90	122.30
	54-860-213-1	2 - 3"/50 - 75mm	0.00005"/0.001mm	0.0002"/0.005mm	164.40	139.70

26

54-860-214-1

3 - 4"/75 - 100mm

Prices & Specifications are subject to change without notice.

0.00005"/0.001mm

0.0002"/0.005mm

185.80

157.90



ange	List Price	Sale Price
- 3" with standards and fitted Shop-Hardened case	\$173.04	\$114.00
- 4" with standards and fitted Shop-Hardened case	222.21	157.60
- 6" with standards and fitted Wooden Case	342.38	250.00
<ul> <li>12" with standards and fitted Wooden Case</li> </ul>	1028.38	616.50
12" with standards and fitted Wooden Case	705.38	419.00
-	3 <sup>°°</sup> with standards and fitted Shop-Hardened case 4" with standards and fitted Shop-Hardened case 6" with standards and fitted Wooden Case 12" with standards and fitted Wooden Case	3" with standards and fitted Shop-Hardened case       \$173.04         4" with standards and fitted Shop-Hardened case       222.21         6" with standards and fitted Wooden Case       342.38         12" with standards and fitted Wooden Case       1028.38

Prices & Specifications are subject to change without notice.

5

media 

**Fowler-Bowers Bluetooth** XTH3 Holematic Pistol Grips

FREE Tablet with the purchase of **ANY Bluetooth Set!** 

NEW!

## **NEW** Larger Display! **NEW** Ergonomic Design! **NEW Four Presets!**

## **BEST** Results in Gage R & R Studies

- · Self centering heads
- USB connectivity and Bluetooth
- Fixed anvils
- Resolution: 0.00005" /0.001mm
- · To reduce hand fatigue, the travel of the Holematic trigger is adjustable for minimum over travel

Made in ENGLAND

Fowler

PROXIMITY INTERFACE

IP67

- Tungsten carbide measuring faces on all 3-point heads from 0.5" (12.5mm) and up.
- Sizes over 0.500" (12.5mm) feature blind bore capability
- · Includes UKAS certificates for all pistol grip, heads and rings
- · Contact the Fowler Technical Department for special anvil applications.

#### \*Bluetooth sets at Non-Bluetooth set prices

ι.	Complete Range	Sets				
	Order No.	Range	Includes	List Price	Sale Price	
	54-567-009-BT	0.080" - 0.250"/2 - 6mm	5 heads, 1 handle, 3 rings	\$6016.98	\$4750.00	
	54-567-010-BT	0.250" - 0.375"/6- 10mm	2 heads, 1 handle, 1 ring	2359.26	1845.00	
П	54-567-020-BT	0.375" - 0.750"/10 - 20mm	3 heads, 1 handle, 2 rings	2760.12	2185.00	
	54-567-050-BT	0.750" - 2" /20 - 50mm	3 heads, 1 handle, 2 rings	3563.88	2870.00	
	54-567-100-BT	2 - 4"/50 - 100mm	3 heads, 1 handle, 2 rings	3966.78	3210.00	
П	54-567-105-BT	4 - 6"/100 - 150mm	2 heads, 1 handle, 1 ring	3563.88	2870.00	
-	54-567-110-BT	6 - 8" /150 - 200mm	2 heads, 1 handle, 1 ring	4704.24	3840.00	
	54-567-200-BT	4 - 8" /100 - 200mm	4 heads, 1 handle, 2 rings	7446.00	6170.00	
Г	54-567-210-BT	0.750" - 4" /20 - 100mm	6 heads, 1 handle, 4 rings	5799.72	4770.00	
H	54-567-620-BT	0.250" - 0.750" 76 - 20mm	5 heads, 1 handle, 3 rings	3289.50	2635.00	
	Connectivity Kit	s				
П	Order No.	Description				
	54-115-526-0	Proximity cable with USB connection		\$136.07	\$122.00	
	54-115-527-0	Proximity cable with serial connection		136.07	122.00	
	54-115-246-BT	USB bluetooth receiver		47.33	42.60	

28

DWIEr TOOL-A-THON Vol. 17.1

# Fowler-Bowers XT-Series Holemikes

The Fowler-Bowers range of mechanical two and three point bore micrometers are now available as XT extended travel holemikes, allowing a wide measurement range without the need to interchange anvils.

# **SPECIAL DEAL!**

Features:

- 3-pt contact with tungsten carbide measuring anvils above 0.5"
- · Blind bore measuring above 0.5"
- · Ratchet stop for consistent measuring
- · Extensions available for deep measuring
- Includes UKAS certificates for all Holemikes and setting rings



Free Special Sylvac Ultra Cal IV with Holemike purchase! \$138.00 Value

(features round depth rod)

				Meas.	Ring	List	Sale
Order No.	Range	Grads.	Accuracy	Depth	Included	Price	Price
52-255-310-0	0.250" - 0.312"	0.00025"	0.00015"	2.28"	0.312"	\$709.21	\$531.00
52-255-311-0	0.312" - 0.375"	0.00025"	0.00015"	2.28"	0.312"	656.68	492.00
52-255-312-0	0.375" - 0.500"	0.00025"	0.00015"	2.28"	0.5"	656.68	492.00
52-255-313-0	0.500" - 0.625"	0.00025"	0.00015"	2.44"	0.5"	656.68	492.00
52-255-314-0	0.625" - 0.750"	0.00025"	0.00015"	2.44"	0.75"	673.40	505.00
52-255-315-0	0.750" - 1"	0.00025"	0.00015"	2.60"	0.75"	739.60	554.00
52-255-316-0	1" - 1.375"	0.00025"	0.00015"	2.60"	1.375"	1053.76	790.00
52-255-317-0	1.375" - 2"	0.00025"	0.00015"	3.15"	1.375"	1078.96	809.00
52-255-318-0	2" - 2.625"	0.00025"	0.0002"	3.15"	2.625"	1287.04	965.00
52-255-319-0	2.625" - 3.250"	0.00025"	0.0002"	3.15"	2.625"	1298.56	973.00
52-255-320-0	3.250" - 4"	0.00025"	0.0002"	3.94"	3.25"	1620.07	1215.00

#### Fowler-Bowers XT-Series Holemike Sets

Order No. Range Includ		Includes	List Price	Sale Price
52-255-565-0	0.250" - 0.375"	2 heads, 2 handles, 1 ring	\$1574.88	\$1181.00
52-255-665-0	0.375" - 0.750"	3 heads, 3 handles, 2 rings	1793.36	1345.00
52-255-775-0	0.750" - 2"	3 heads, 3 handles, 2 rings	2817.75	2113.00
52-255-885-0	2" - 4"	3 heads, 3 handles, 2 rings	3820.00	2865.00
	52-255-565-0 52-255-665-0 52-255-775-0	52-255-565-0         0.250" - 0.375"           52-255-665-0         0.375" - 0.750"           52-255-775-0         0.750" - 2"	52-255-565-0         0.250" - 0.375"         2 heads, 2 handles, 1 ring           52-255-665-0         0.375" - 0.750"         3 heads, 3 handles, 2 rings           52-255-775-0         0.750" - 2"         3 heads, 3 handles, 2 rings	52-255-565-0         0.250" - 0.375"         2 heads, 2 handles, 1 ring         \$1574.88           52-255-665-0         0.375" - 0.750"         3 heads, 3 handles, 2 rings         1793.36           52-255-775-0         0.750" - 2"         3 heads, 3 handles, 2 rings         2817.75




## **DEPTH MICROMETERS**

Find us on social media!



Order No.	Range	Graduation	Base	List Price	Sale Price
52-225-110-0	0 - 4"	0.001"	2.5"	\$129.92	\$113.00
52-225-112-0	0 - 6"	0.001"	2.5"	160.83	137.00
52-225-114-0	0 - 4"	0.001"	4"	140.34	122.00
52-225-116-0	0 - 6"	0.001"	4"	164.42	142.00

#### **Digit Counter Depth Micrometers**



#### **IP54 Electronic Depth Micrometer**

- Resolution: 0.00005"/0.001mm
- Range: 0 6"/150mm
- Hardened tool steel, precision ground
- and microlapped 4" base
- Rod diameter: 0.176
- Large LCD display





List \$218.25

Order No. 54-225-456-0

ale

Fowler TOOL-A-THON Vol. 17.1

30

Prices & Specifications are subject to change without notice.

\$170

	ICATING MIC		5
		52-245-50	
Wider Micro-Fine gr Carbide tipped anvil Retracting button co operator's hand	rdened and precision ground aduations I & spindle nveniently located in relation to	<ul> <li>0-1" Range, head graduated</li> <li>Dial graduated in 0.00005"</li> <li>Indicated accuracy of 0.000</li> <li>Diameter of spindle: 0.256"</li> </ul>	
Wider Micro-Fine gr Carbide tipped anvil	aduations	Dial graduated in 0.00005"     Indicated accuracy of 0.000     Diameter of spindle: 0.256"     List Price	

#### **Electronic Indicating Micrometers**

A superior tool in quality and design, the Fowler/Bowers Electronic indicating Micrometer operates guickly and easily.



Order No.	Description	List Price	Sale Price
54-245-777-0	0 - 1.25"/0-30mm	\$1208.19	\$1020.00
54-245-780-0	1.25" - 2.50"/30-60mm	1434.12	1200.00


Prices & Specifications are subject to change without notice.

31





# **ID - OD MEASURING**



Ter TOOL-A-THON Vol. 17.1

Find us on social media!

34

nside Micromete	ers
	52-275-005-0
0.2- 1.2" 0.001"	
2109876543 1.1.1.1.1.1.1.1.1.1.1 1000000000000000	0 Fowler
	52-275-001-1
0.2"	<ul> <li>Measuring faces are fully hardened, precision ground and microlap finished to assure exceptionally accurate measuring</li> <li>Spindle threads are hardened and ground</li> <li>Microfine graduations 0.001" on a satin chrome finish permit</li> </ul>
	easy reading <ul> <li>Ratchet stop thimble assures exact and repetitive readings</li> <li>Includes a setting ring</li> </ul>

Order No.	Range	Graduation	Accuracy	List Price	Sale Price
52-275-001-1	0.2" - 1.2"	0.001"	0.0002"	\$109.32	\$80.00
52-275-002-1	1" - 2"	0.001"	0.0002"	117.72	87.00
52-275-005-0	0.2" - 2.2"	0.001"	0.0002"	184.80	155.00

#### **Electronic IP54 Inside Micrometer**

02- (Formation 54		ONOFF-SET ABS/INC-UNIT		
			0.2"	<b>F</b> ind
Each gage in	ncludes setting ring	ations		
<ul> <li>Large easy-t</li> <li>Friction thim</li> </ul>				on so
<ul> <li>Includes set</li> </ul>	ung ring			social r
Order No.	Range	Accuracy	List Price Sale Price	
54-860-275-0 54-860-276-0	0.2 - 1.2" 1 - 2"	0.00020"/0.005mm	\$231.19 <b>\$170.00</b> 250.58 <b>185.00</b>	

Order No.	Range	Accuracy	List Price	Sale Price
54-860-275-0	0.2 - 1.2"	0.00020"/0.005mm	\$231.19	\$170.00
54-860-276-0	1 - 2"	0.00024"/0.006mm	250.58	185.00

**I. 17.1** 

#### **CYLINDER BORE GAGES** Dial Bore Gage Sets with Carbide Anvils Carbide anvils · Easy-to-read Economical Insulated grip Includes extension holder and fitted case

52-646-100-0

0.0005"

Graduation

Graduation

0.0005"

0.0001"

0.01mm

52-646-300-0

Sale Price

\$110.00

2

Sale Price

List \$320.33

\$110.00

173.50

List Price

52-646-400-0

List Price

\$185.40

231.75

204 07

\$147.60

3

2

D

Order No.

Order No.

52-646-400-0

52-646-500-0

E0 646 000 0

52-646-100-0

Range

Description

Inch X-Tender Bore Gage Set

Inch X-Tender Bore Gage Set

Motrie V Tender Pere Gage Set

0.7 - 1.5"



52-646-220-0	Metric X-Tender	Bore Gage Se	t	0.01	nm		204.	.87	120.00
Extender								_	
Preset size of musice as the gage	aster for absolut is rocked in the	te reading a	nd us neasu eature -6"/35i ils ng	e mini Ired. es: mm-15	i <b>mum hc</b> Omm		re to l		the bore
ABS BBB 18 Inmm ABS/SE MIN	165m	ndicator Fea Bar graph au display Resolution: ( Preset with n ABS/INC me Min/Max/TIF	nd nun 0.0000 recall easure	neric d )5"/0.0	Ŭ (				
		Fo " <mark>X-tende</mark> No. 54-64	r Bor	e Gag		deo sea vww.yo		e.com	6

Sale \$25

36



#### **Test Indicators**

All Fowler Test Indicators include bi-directional constant clockwise rotation, automatic reversal, three dovetail mountings, jeweled movement, two dovetail clamps and a molded case.



Order	Face	Total	Dial		Dial	Point	List	Sale
No.	Color	Range	Reading	Graduation	Diameter	Length	Price	Price
52-562-774-0	white	0.030"	0-15-0	0.001"	1"	1/2"	\$111.76	\$75.00
52-562-778-0	black	0.030"	0-15-0	0.0005"	1"	1/2"	118.76	75.00
52-562-775-0	white	0.030"	0-15-0	0.0005"	1"	1/2"	118.76	75.00
52-562-776-0	white	0.030"	0-15-0	0.0005"	1-1/2"	1/2"	124.22	75.00
52-562-780-0	black	0.030"	0-15-0	0.0005"	1-1/2"	1/2"	124.22	<b>75.00</b>



Order	Face	Total	Dial		Dial	Point	List	Sale
No.	Color	Range	Reading	Graduation	Diameter	Length	Price	Price
52-563-770-0	white	0.008"	0-4-0	0.0001"	1"	1/2"	\$118.76	\$90.00
52-563-771-0	black	0.008"	0-4-0	0.0001"	1"	1/2"	118.76	90.00
52-563-777-0	white	0.008"	0-4-0	0.0001"	1-1/2"	1/2"	118.76	90.00
52-563-772-0	black	0.008"	0-4-0	0.0001"	1-1/2"	1/2"	118.76	90.00



Order No.	Face Color	Total Range	Dial Reading	Graduation	Dial Diameter	Point Length	List Price	Sale Price
52-562-781-0	white	0.020"	0-10-0	0.0005"	Jameter	1-7/16"	\$122.36	\$95.00
					1.			
52-562-782-0	black	0.020"	0-10-0	0.0005"		1-7/16"	122.36	95.00
52-562-783-0	white	0.020"	0-10-0	0.0005"	1-1/2"	1-7/16"	122.36	95.00
52-562-784-0	black	0.020"	0-10-0	0.0005"	1-1/2"	1-7/16"	122.36	95.00

Find us on social media!

j

**.** 

IJ

4-



Order No.	Style	Graduations	Dial Diameter	Dial Reading	List Price	Sale Price
52-562-001-0	Horizontal	0.0005"	1-1/2"	0-15-0	\$124.73	\$100.00
52-562-002-0	Horizontal	0.0005"	1"	0-15-0	127.73	100.00
52-562-003-0	Horizontal	0.001"	1"	0-15-0	127.73	100.00
52-562-004-0	Vertical	0.0005"	1-1/2"	0-15-0	136.58	100.00
52-562-005-0	Vertical	0.0005"	1"	0-15-0	136.58	100.00
52-562-006-0	Vertical	0.001"	1"	0-15-0	136.58	100.00
52-562-007-0	Horizontal	0.01mm	25mm	0-40-0	124.94	100.00
52-562-008-0	Horizontal	0.01mm	38mm	0-40-0	124.94	100.00



## Multimode Electronic Test Indicators

The QuadraTest is the perfect solution to test indicating applications.

4 measuring modes: Min, Max, TIR and Direct

- 4 measuring resolutions 0.00005"/0.001mm or 0.0005"/0.01mm
- Water, oil and coolant resistant to IP65
- 1-1/2" diameter dial face rotates a full 360°
- Bar graph and numeric digital display.
- Meets or exceeds DIN/ISO Standards.
   (Maximum error on 00005" and at fin
- (Maximum error on .00005" scale at full range: 0.0004") • Available with 1/2" or extra-long 1-7/16" contact point.

54-562-777-0

00

MODI

vivac

Order No.	Range	Contact Point Length	List Price	Sale Price
54-562-777-0	0.040"/1mm	1/2"	\$224.91	\$195.00
54-562-888-0	0.020"/0.5mm	1-7/16"	332.01	300.00
Accessories				
54-115-528-0	Output Cable USB		\$231.13	\$218.00



Example Find us on social medial

-owler

**RS-232** 

DIRECT

-owler

POWER

P65



- .080" & .040" contact points
- Universal clamp
- · Height gage attachment
- 3/8" & 1/4" dovetail clamps
- · Manufacturer's test certificate

#### Order No. 52-562-999-0




List \$121.28



Find us on social media!

40



Order No.	Range	Graduation	Reading	Balanced Reading	Dial Color	List Price	Sale Price
52-520-110-1	NEW 1"	0.001"	0 - 100	-	Black Face	\$87.55	\$65.00
52-520-110-2	NEW 1"	0.001"	0 - 100	-	White Face	87.55	65.00
52-520-105-0	NEW 0.500"	0.001"	0 - 100	0 - 50 -0	White Face	82.81	62.00
52-520-120-0	<b>NEW</b> 2"	0.001"	0 - 100	0 - 50 - 0	White Face	135.45	101.50
52-520-129-0	NEW 1"	0.0005"	0 - 50	0 - 25 - 0	White Face	105.88	79.00
52-520-135-0	NEW 0.05"	0.0001"	0 - 10	0 - 5 - 0	White Face	151.72	113.50
52-520-125-0	NEW 0.250"	0.0005"	0 - 50	0 - 25 - 0	White Face	115.57	86.50
52-520-500-0	NEW 25mm	0.01mm	0 - 100	0 - 50 - <mark>0</mark>	White Face	133.28	99.00

X-PF	<b>200</b> f	<sup>®</sup> IP54	Shock	proof Dia		ators
					-SERIES	
<ul> <li>Protection</li> <li>Rubber be</li> </ul>		em				
<ul> <li>O-ring sea</li> <li>O-ring prot rotating dia</li> </ul>	tection for b			A DESTRICT 20	90	9 20 Former #20
Sealed bac				ante serie	70×	
Specification	f design		1		and and a second s	
Continuous     Tolerance r		-100				
AGD Group     Lugback ar	p 2, 2-1/4" c		52-520-450	5.0	2-520-455-0	
				U		U
Order No. 52-520-450-0	Range	Graduation 0.001"	Reading 0 - 100	<u>Contact Point</u> 4 - 48 (3/8" stem)	List Price \$73.65	Sale Price \$47.50
52-520-450-0	1	0.001	0-100	4 - 40 (3/0 31011)	\$75.05	\$47.50

Prices & Specifications are subject to change without notice.

4 - 48 (3/8" stem)

0 - 100

1"

0.001"

52-520-455-0

79.62

-

Π

5

us on social media





## INDI-MAX Electronic Indicators

IP54 Coolant & fluid resistant

- Auto Off feature
- 2-1/4" dial face
- 3/8" stem 4-48 thread
- Resolution 0.00005"/0.001mm
- Accuracy: 0.00016"/0.004mm (to 1")
- Tolerance indicators
- Absolute/incremental reading
- Lugback supplied on 1/2" model



54-520-310-0

54-520-320-0

Protected to:

COOLANT & FLUID RESISTANT

Fowler

PRESET

TOL

in/mm

ZERO/ABS

## Carbide-tipped points!

Order No.	Description	List Price	Sale Price
54-520-305-0	0.5"/12.5mm Indi-Max	\$338.90	\$240.00
54-520-310-0	1"/25mm Indi-Max	380.10	265.00
54-520-320-0	2"/50mm Indi-Ma	493.40	350.00
52-525-605-0	Lugback for 1" and 2" models	16.70	12.25
54-520-399-0	Data cable	152.90	140.00
54-115-100-0	NEW Wireless Transmitter Kit - See Page 20	99.50	89.50

54-520-305-0

Fowler





Find us on social media!

Prices & Specifications are subject to change without notice.

44

## **MAGNETIC BASES Deluxe Dial Gage Stand** W/er Quick positioning and adjustment Fine adjustment of 5/32" Holds indicators with stems of 3/8" and 8mm Range 5"/125mm Working surface of 3-1/2" x 3-1/2" Overall Height: 8.5" TOOL-A-THON Vol. 17.1 Order No. 52-580-015-0 Fowler Sale \$255\_00 List \$306.29 **Granite Dial Gage Stand** Sturdy and compact with extreme stability 6" x 6" x 2" granite base Positive lock screw Fine adjustment knob for zero setting Column height is 8" Accepts all lug-back indicators This stand is maintenance free Flatness: 0.00005" Indicator not included with stand Order No. 52-580-030-0 Sale \$79.00 List \$116.55 **High Precision Dial Gage Stand** Quick positioning and adjustment Extra Long Column Features fine adjustment of 5/32" Total height of column 14" Can hold indicators with stems of 3/8" and 8mm Supplied with two 2-3/8" diameter anvils, flat and serrated us on social П 5

Order No. 52-580-014-0



Prices & Specifications are subject to change without notice.

45

**S** 

## **MAG BASE & INDICATOR COMBOS**

More flexibility than flex-arm type base!

Can be set up in almost unlimited positions!



46

52-585-008-0

Prices & Specifications are subject to change without notice.

94.97

85.00

Articulating Mag Base only



Prices & Specifications are subject to change without notice.

47

## PROTRACTORS

#### **Mini-Mag Plus** The NEW Mini-Mag PLUS Protractor features a USB rechargeable battery, a backlit display, Tilt% function and IP54 protection against water, oil, and fluids. · IP54 protected against debris and fluids · USB rechargeable battery with status light (cable included) NEW! Backlit display Tilt % function Auto off after 5 minutes Fowler mint-MAG PLUS Embedded magnets Measuring range: 360° (4 x 90) Display automatically inverts Resolution: 0.05° Accuracy: ± 0.2° Repeatability: 0.05° rotected Hold feature Zero function İD54 • Smaller size: 2.12" x 2.12" x .9" HOLD Light weight: 2.7 oz. ESISTAN Tilt%

Order No. 54-422-500-0



## G Protractor

The mini-MAG Protractor provides instant 360° digital inclination display of any angle with the additional unique feature of embedded magnets on both sides and the bottom which make it ideal for a variety of measurements.

· Embedded magnets with 3.5lb, pull Uses standard 9V battery (250 hrs.) Measuring range: 360° (4 x 90°) · Display automatically inverts Resolution: 0.05° Accuracy: ± 0.2° Repeatability: 0.05° Dimensions 2.375" x 1.375" x 2.375" Display inverts for easy reading! Hold feature OOL-A-THON Order No. 54-422-450-1 BEST SELLEK Sale \$ List \$94.97 WLER HIGH **Magnetic Dial Protractor** NEW! Magnets Hold at Any Angle! · Both flat and "V" mounting with strong built-in magnet Punch located at center of "V" 1° graduations and accuracy Supplied with extra punch Order No. 52-450-100-0 25\_00

Find us on social media!

3

2

1)

4-

48

Prices & Specifications are subject to change without notice.

List \$140.00



## **SHOP TOOLS**

#### **Electronic Edge Finders**

- · Six equally spaced light ports provide visibility at any angle
- Made in the USA

Find us on social media!

j

**.** 

D

4-

· Edge finder lights instantly when stylus touches work edge

0.400"

· Repeatability: 0.0002"

54-575-650-0

· Works on any conductive metal



3/4"

91.00

116.75

54-575-625-0

54-575-600-0

					-	54-575-650-0
Along with light	ht indication	, model #54-5	575-650-0 emit	s an audible "b	peep" at time	of contact.
Order No.	Stylus	Shank	Audible	Battery	List Price	Sale Price
54-575-600-0	0.200"	1/2"	NO	12 volt	\$33.11	\$25.00
54-575-625-0	0.200"	1/2"	NO	12 volt	116.75	91.00

YES

12 volt



Order No.	Description	List Price	Sale Price
52-415-020-0	NEW 1.5" Center Finder	\$17.00	\$15.00
52-415-025-0	NEW 3" Center Finder	19.00	17.00

#### **2** Dimensional BEST SELLER **Coaxial Indicator Sets**

Use the 2D Coaxial Set for accurate component centering and positioning in most machining applications. The dial remains stationary during the rotation of the machine spindle.

- · Indicator assembly with 1.6" (42.5mm) diameter dial
- Graduations and revolution counter 0.0005" (.01mm)
- 3 Internal and 3 External feelers · Center point feeler
- Restraining arm

#### Specifications:

- Length: 6-7/8" (175mm)
- Shank: 3/8" dia. x 7/8" (10mm x 20mm) long Feeler ball: 1/8" (3mm) dia.
- Dial readings: 0-50
- Measuring range: 0.250" (6mm) axis offset
- Speed—recommended not to exceed approx. 800 RPM
- Repeatability to within 0.0002" (0.005mm) of true center
- Capacity depends on feelers installed, but overall range is 5/32-12" (4-300mm) internal diameter; 0-12" (0-300mm) external diameter

52-710-025-0

Order No.	Description	List Price	Sale Price
52-710-025-0	2D Coaxial Set-Inch	\$238.99	\$160.50
52-710-030-0	2D Coaxial Set-Metric	243.67	173.80



## **SHOP TOOLS**

IN USA 4

#### RULES

- **EZ-Read Black Face Rules**
- · Hardened stainless steel · White easy-to-read microfine graduations against a black, non-glare finish

52-297-006-0 64THS 16 24 32 40 48 56 8 16 24 32 40 48 56

#### 52-330-006-0

wier 3

#### Satin Chrome Rules

- Tempered steel
- Non-glare
- Sharp, easy-to-read microfine graduations

5

#### **Golden Rules**

- · Titanium coated for superior wear resistance
- Non-glare finish=RC80
- Scratch resistant microfine graduations with excellent clarity and contrast

#### GRADUATIONS 4R: 8ths, 16ths, 32nds, 64ths 6R: 32nds, 64ths, 50ths, 100ths

.4

52-299-006-0

Order No.	Finish	Size	Reading	List Price	Sale Price
52-330-006-0	Satin Chrome	6"	4R	\$11.72	\$10.00
52-337-006-0	Black	6"	4R	9.89	8.40
52-339-006-0	Golden	6"	4R	24.40	20.75
52-330-012-0	Satin Chrome	12"	4R	20.32	17.30
52-337-012-0	Black	12"	4R	20.32	17.30
52-339-012-0	Golden	12"	4R	46.76	39.75
52-350-006-0	Satin Chrome	6"	16R	10.97	9.00
52-338-006-0	Black	6"	16R	9.89	8.20
52-350-012-0	Satin Chrome	12"	16R	18.92	15.50
52-338-012-0	Black	12"	16R	14.84	12.50

linininininini."

FLEXIBLE STEE	L RULES				
Order No.	Finish	Size	Reading	List Price	Sale Price
52-295-006-0	Satin Chrome	6"	4R	\$11.29	\$9.60
52-297-006-0	Black	6"	4R	9.25	7.85
52-299-006-0	Golden	6"	4R	23.97	20.30
52-295-012-0	Satin Chrome	12"	4R	17.31	15.00
52-297-012-0	Black	12"	4R	14.19	12.50
52-299-012-0	Golden	12"	4R	43.00	36.55
52-308-006-0	Black	6"	16R	9.46	8.00
52-310-006-0	Satin Chrome	6"	16R	11.29	10.00
52-308-012-0	Black	12"	16R	14.19	12.00
52-310-012-0	Satin Chrome	12"	16R	16.56	14.00

## **Combination Square**

- · Blades are chrome plated, fully hardened and tempered
- · Includes square, protractor and center head with 12" blade
- Square head has level and scriber point
- · Double indexed protractor is graduated 180° in both directions
- · Graduated in 8ths, 16ths, 32nds and 64ths

#### Order No. 52-370-012-0





A-THOA BEST SELLER!


WLER HIGH



Find us on social media

52

## SHOP TOOLS



## **Etching Pen**

#### ETCHING MARKER Fowler Tint

A "must" for any tool room and machine shop for general marking purposes, Fowler's metal etching pen is used on copper, copper alloy, stainless steel, hardened steel tools and castings, etc. Use it to initial personal tools or to restore graduations on rules, height gages, calipers, micrometers, etc. Its low-cost, disposable design offers limitless applications.

Order No. 52-730-005-0



## Thickness Gages

- Each leaf of the thickness gage made of fine tempered steel, hardened
- The exact thickness is marked on each leaf
- Steel case with lock nut
- Meets U.S. Federal Specifications



52-485-010-0

Order No.	Description	List Price	Sale Price	
52-485-006-0	Tapered Thickness Gages-Inch 26 Leaf Set: 0.0015", 0.002", 0.0025", 0.003	", \$16.56	\$14.25	
	0.004", 0.005", 0.006", 0.007", 0.008", 0.009", 0.010", 0.011", 0.012", 0.013",			
-	0.014", 0.015", 0.016", 0.017", 0.018", 0.019", 0.020", 0.021", 0.022", 0.023"	,		
	0.024" and 0.025".			
-	Length: 3".			
52-485-010-0		18.90	11.00	
	0.15mm, 0.20mm, 0.25mm, 0.30mm, 0.35mm, 0.40mm, 0.45mm,			
-	0.50mm, 0.55mm, 0.60mm, 0.65mm, 0.70mm, 0.75mm, 0.80mm,			
	0.85mm, 0.90mm, 0.95mm and 1mm. Length: 100mm.			

## Screw Pitch Gages

- Narrow designed blades permit use for internal and external screw threads
- Locking device at each end to secure all blades for storage or position
- Correct pitch is determined by matching blade teeth with threads
- Precisely ground and finished
- Blades marked with thread size

Order No.	Description	List Price	Sale Price
Inch Series			
52-485-015-0	Screw Pitch Gage with 30 blades: 4 to 42 pitch standard V thread	\$11.34	\$9.50
Metric Series	ů i		
52-485-020-0	Screw Pitch Gage with 24 blades: 0.25mm to 6.0mm	11.34	9,50

us on socia

5

Ī

W/er

52-485-015-0

## LEVELS

#### **Fowler-Wyler Clinotronic Plus**

The Fowler-WYLER Clinotronic Plus is an electronic level with unsurpassed versatility. It is economically priced, uses a specially designed microprocessor and the well-proven WYLER inclination sensor.

#### Features:

Find us on social media!

j

**.** 

11

4-

- Range of ± 45°, capacity of 0-360°
- Resolution of 0.01° (selectable) Uses standard 1.5v AA batteries
- Absolute or relative measuring mode selectable by
- push button Seal-tec technology for excellent performance even in
- difficult environmental conditions
- Interface connection RS-232 is integrated. Special purpose cables available
- No loss of calibration data by power failure

#### **Technical Specifications:**

- · Response time: value available within 5 seconds Repeatability: <.01°</li>
- Linearity: within 3 min. of arc
   Battery: Standard AA 1.5V alkaline/130hrs or AA 3.0V Mn02-Lithium (for longer operation 300/hrs)
- Housing: aluminum hard anodized.
- Dimensions: 4 x 3 x 1"(100 x 75 x 30mm)
- Temp. range: operational 0 to 40°C




The following measuring units may be aalaatad

selectea:			
Deg/Arcmin			00'
Arcmin / Arcsec		00'	00"
GON / Neugrad (2 [	Dec)	00.00	gon
GON / Neugrad (4 [	Dec)	.0000	gon
mm / rel.Basis (2 De		.00 mn	n/m
mm / rel.Basis (4 De	ec) (oe	)00 mn	n/m
Inch / rel.Basis (4 D	ec) .	0000"/	10"
artillery per mille A%	00	- 0	000
mm / m (2 Dec)	00	.00 mn	n/m
Inch / 10 Inches		0000"/	10"
Inch / 12 Inches		0000"/	12"
Milliradian	00.00 mr	ad (2D	ec)
Milliradian	0	0000 m	rad
Deg (2 Dec)		00.0	00 °
Deg (4 Dec)		.00	00°



## **Fowler-Wyler Frame Spirit Levels**

Sensitivity 0.0005" per 10". The level features two prismatic sides and also comes equipped with insulating handles.



			Sensitivity	Overall			L
Order No.	Inch	Metric	Angular	Dimensions	List Price	Sale Price	t
53-422-057-0	0.0005"/10"	0.05mm/m	10 sec.	6" x 1-3/8" x 6"	\$1622.00	\$1350.00	L
53-422-058-0	0.0005"/10"	0.05mm/m	10 sec.	4" x 1-3⁄8" x 4"	1443.50	1200.00	L
53-422-059-0	0.0005"/10"	0.05mm/m	10 sec.	7-7/8"x 1-9/16"x 7-7/8"	1996.14	1600.00	ŀ

## **SCANS**

# Scan 52

First horizontal SCAN machine specially designed for workshop measurement close to the machine-tool. The concept is to measure the parts in the same position as they are machined.

SYLVAC SCAN 52

Suitable for first-off part, control in process (SPC), sampling or 100% inspection, our Sylvac SCAN 52 machines are set to revolutionize the control in workshop.

HIIII

#### Includes:

- Instrument according to technical
- specifications 2 male centers
- Computer
- Mouse
- Keyboard
- Windows multilingual operating system Screen
- Manual
- Sylvac Reflex-Scan Software
- Rotary headstock (on model 54-902-552-1)

#### When measuring becomes a breeze!

Place the workpiece on the SCAN machine, click the button and get all the values automatically and without prior programing. Perfectly integrated in the workshop, our SCAN 52 machines replace conventional measuring systems including multi-gauging jigs.

<u>Reflex Click</u> The measuring system that makes everyone an expert !

NEWY

#### **TECHNICAL SPECIFICATIONS**

REFLEX-CLICK

		54-902-552-0		54-902-552-1	
	_	Diameter	Length	Diameter	Length
Measuring range	(mm)	0.5 ÷ 52	300	0.5 ÷ 52	300
Numerical interval	(mm)	0.0001	0.0005	0.0001	0.0005
Accuracy	μm	(1.5 + D/100)	(4 + L/100)	(1.5 + D/100)	(4 + L/100)
Repeatability	μm	0.5	2.5	0.5	2.5
Rotary headstock				1	/
Weight	kg		1	03	_

#### Other styles, sizes and sensitivities are available upon request.

Order No.	Description	List Price
54-902-552-0	NEW Scan 52 without rotary headstock	\$34,136.34
54-902-552-1	NEW Scan 52 with rotary headstock	39,765.72





# HIGH PRECISION www.fowlerprecision.com